

A multi-purpose STOU tractor oil, enabling you to use the same oil for the engine, mechanical transmissions and hydraulic controls.

PERFORMANCES

Meets the requirements of the following specifications:

Moteur:

API CG-4/SG
ACEA E4-08
MIL-L-2104D/MIL-L-46152B
FORD M2C-159A

Spécifications:

MB 228.3/228.1/227.1
MAN 271

Transmission :

API GL-4
MIL-L-2105
FORD M2C-159b
MASSEY FERGUSON M-1139/M-1145

ALLISON C-4
CATERPILLAR TO-2
JOHN DEERE JDM J27
ZF TE-ML 06B, 06C, 06D, 06F, 06Q, 06R

Hydraulique :

ISO-L-HV 68

ADVANTAGES

Thanks to its special additives, PRO MULTI can grease supercharged and non-supercharged petrol or diesel engines, as well as axles equipped with immersed brakes, and can also be used as a hydraulic fluid.

USES

Lubricating petrol or diesel tractor engines.

Mechanical and hydraulic transmissions on any tractors and threshing harvesters where the manufacturer recommends using a multi-purpose oil.

Characteristics	Methods	Units	15W-30	15W-40
Density at 15°C	NF T 60-101	kg/m ³	888	886
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	78.6	102.8
Viscosity index	NF T 60-136	-	130	138

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.