

A synthetic lubricant specially developed for very high performance 2-stroke engines.

PERFORMANCES

Standards:

JASO FC – Anti-smoke

JASO FD – High detergency level

ISO-L-EGD

ADVANTAGES

PROFIL EXTREME 2T meets standard JASO FD:

- less polluting
- guaranteed low engine clogging rate (which improves combustion and extends the lifetime of your exhaust box)
- reduced smoke emissions.

PROFIL EXTREME 2T contains synthetic bases, especially viscous esters, replacing the thick petroleum bases in general use.

These viscous esters provide better lubricating properties, which prevents risks of tightening, with no formation of carbon deposits by burning, which ensures high cleanliness of the piston grooves, segments and exhaust ports.

Synthetic to enable better combustion and keep the engine clean, in separate greasing or in mixture with petrol.

In case of mixture, use 2 % to 4 % (according to manufacturer's recommendations).

Fuel	Dose 2% (50:1)	Dose 3% (33:1)	Dose 4% (25:1)
1 litre	20 ml	30 ml	40 ml
2 litres	40 ml	60 ml	80 ml
5 litres	100 ml	150 ml	200 ml
10 litres	200 ml	300 ml	400 ml

Technical data sheet

USES

PROFIL EXTREME 2T has been developed for all high-performance 2-stroke engines fitted in mechanised gardening equipment.

Characteristics	Methods	Units	Profil Extreme 2T
Colour	Visual		Blue
Density at 15°C	NF T 60-101	kg/m ³	881
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	52
Kinematic viscosity at 100°C	NF T 60-100	mm ² /s	8.7
Viscosity index	NF T 60-136	-	145
COC flash point	NF T 60-118	°C	90
Pour point	NF T 60-105	°C	-43

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: II-55-1503
Published: 26/07/2016