

**A complex calcium sulfonate type lubricating grease.**

**PERFORMANCE**

DIN 51502: KP2N-20

ISO 6743 / 12924: L-XC(F)DIB2

Category H1, NSF registration: pending

Drop point: > 280°C

EP Welding: = 6500 N

Uses: -20°C to +140°C (max. +180°C)

**ADVANTAGES**

Presence of water

Lubricating power maintained even in the presence of large quantities of water. Exceptional adhesiveness on metal in wet environments.

Mechanical stability

Good mechanical strength even in the presence of water

EP

Excellent EP properties and ability to withstand high loads (inherent in type of soap).

High base oil viscosity

For use at low speeds and high loads

**USES**

Agri-business

Machinery under high stress

Plain bearing blocks and gears

Components subject to low loads at low speed, including at high temperatures (max. 180°C)

Fiche technique



Characteristics	Standards	Units	Values
Colour	-	-	Chestnut brown
Texture	-	-	Smooth
Density	IP530	kg/m <sup>3</sup>	1020
Nature of base oil	-	-	White mineral
Base oil viscosity at 40°C	ASTM D 7152	mm <sup>2</sup> /s	460
Base oil viscosity at 100°C	ASTM D 7152	mm <sup>2</sup> /s	40
NLGI grade	-	-	2
60-stroke penetration	ISO 2137	1/10 mm	265/295
Drop point	IP396	°C	> 280
4-ball weld	DIN 51350:4	N	6500
Water resistance at 90°C	DIN 51807:1	-	1
Water washout at 79°C	ISO 11009	%	<10
Emcor	ISO 11007	-	0-0

# Fiche technique

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: X-IGOL014-1807  
- Published: 12/07/18

