

Corrosion protection fluids

Use:

RUSTOLA 1020 2020 3020 are tailored for protecting all mechanical parts for shipment or storage.

Application by means of immersion, spraying or spreading with a brush

Description:

Oily protective fluids with specific additives to give them a high affinity for metals and water-repellent properties, thus delivering effective protection against corrosion in wet or saline atmospheres.

Characteristics:

Characteristics	Standards	Units	Values		
			1020	2020	3020
Density at 15°C	NFT 60-101	kg/m ³	867	868	869
COC flash point	NFT 60-118	°C	204	210	204
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	22.1	23.2	22.7
Salt spray	-	hours	40-48	52-72	88-96
Film thickness	-	µm	4.0	4.3	4.75
Internal/External protection duration	-	months	0.5/-	6/3	9/6

Fiche technique

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.



Document ref.:
XII-IGOL031-1807
Published: 0/04/2018