

High viscosity index specific lubricants for motorcycle forks.

- Semi-synthetic 10W (MEDIUM)
- Mineral 15W (MEDIUM / HARD)
- Mineral 20W (HARD)

### ADVANTAGES

This fluid is characterized by a **very high viscosity** index allowing a good cold and hot damping effect guaranteeing a consistent performance over time.

The additive system has excellent **anti-foam and anti-oxidant** properties responding to the most severe demands.

### USES

MEDIUM grade 10W is suitable for both **conventional and inverted** forks.

MEDIUM / HARD 15W and HARD 20W are suitable for conventional forks.

Characteristics	Méthods	Units	10W	15W	20W
Color			Red	Red	Red
Density at 15°C	ASTM D4052	g/cm3	0.873	0.876	0.879
Kinematic viscosity at 40°C	ASTM D7042	mm <sup>2</sup> /s	31.8	45.7	67.2
Kinematic viscosity at 100°C	ASTM D7042	mm <sup>2</sup> /s	6.2	7.93	10.32
Viscosity index	-	-	150	145	140
COC flash point	ASTM D92	°C	210	210	210
Pour point	ASTM D97	°C	-42	-36	-30

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XVII-IGOL004-1910  
Published : 15/10/2019

