

High viscosity index specific lubricants for motorcycle forks.

- grade 2.5W (LIGHT)
- grade 5W (LIGHT / MEDIUM)

ADVANTAGES

This fluid is characterized by a **very high viscosity** index allowing a good cold and hot damping effect guaranteeing a consistent performance over time.

The additive system has excellent **anti-foam and anti-oxidant** properties responding to the most severe demands.

USES

Is suitable for both **conventional and inverted** forks.

Possible mixing of LIGHT (2.5W) and LIGHT / MEDIUM (5W) grades as recommended by the manufacturers.

Characteristics	Méthods	Units	2.5W	5W
Color			Red	Red
Density at 15°C	ASTM D4052	g/m ³	0.86	0.87
Kinematic viscosity at 40°C	ASTM D7042	mm ² /s	12.9	21.4
Kinematic viscosity at 100°C	ASTM D7042	mm ² /s	4.9	7.6
Viscosity index	-	-	376	369
COC flash point	ASTM D92	°C	110	108
Pour Point	ASTM D97	°C	-44	-46

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XVII-IGOL003-1910
Published : 15/10/2019

