

Very high performance ester based synthetic lubricant for high performance 2 stroke motorcycle and scooter engines.

PERFORMANCES

TC API: Standard for 2-stroke engine issued by the American Petroleum Institute.

JASO FD: Meets the most demanding requirements in terms of lubrication. Since the FD level is the highest of the **JASO** standard (Japanese standard), the lubricating power, the smoke properties and especially the detergency are higher than the FC level.

ISO-L-EGD: Based on the JASO FD standard with the added bonus of cleanliness on the piston (piston clean test).

ROTAX 253

ADVANTAGES

- ✓ Very stable to oxidation
- ✓ Avoid the risk of tightening
- ✓ Strong wetting power
- ✓ Additivation without ash allowing the control of wear and deposits related to combustion.

ADDITIVE: New generation high performance additives enhance the thermal stability of the lubricant, reduce the risks of high temperature oxidation and reduce oil consumption due to volatility.

USES

PROPULS PERFORMANCE 2T lubricant is compatible with new 2-stroke injection technologies and is suitable for all types of applications: **Speed, Road, Motocross, Enduro and Scooters.**



Suitable for working motors with separate lubrication and mixing.

Mixture: Use 1% to 4% according to manufacturer's recommendations.

Fuel	Dose 1% (100:1)	Dose 2% (50:1)	Dose 3% (33:1)	Dose 4% (25:1)
1 Litre	10 ml	20 ml	30 ml	40 ml
2 Litres	20ml	40ml	60 ml	80 ml
5 Litres	50 ml	100 ml	150 ml	200 ml
10 Litres	100 ml	200 ml	300 ml	400 ml

Characteristics	Méthods	Units	Values
Color			Bleu
Density at 15°C	ASTM D4052	g/cm ³	0.874
Kinematic viscosity at 40°C	ASTM D7042	mm ² /s	66.3
Kinematic viscosity at 100°C	ASTM D7042	mm ² /s	10.9
Viscosity index	ASTM D2270	-	156
Pour point	ASTM D97	°C	-47
COC flash point	ASTM D92	°C	91

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: II-IGOL013-1910
Published : 15/10/2019

Technical data sheet

