

Semi-synthetic lubricant specially for cardan transmission and gearboxes with separate sump.

PERFORMANCES

API GL-4 & GL-5 :

Gear standards operating in moderate to severe speeds and loads with moderate pressure to extreme pressure.

ADVANTAGES

The PROPULS GEAR lubricant has a special additive which gives it very high extreme pressure properties meeting the API GL-4 and GL-5 standards, allowing its use in all mechanical gearboxes, including those equipped with cuprous metals (no action. corrosive).

USES

Lubricant designed for gondolas and transmissions, separate gearboxes and scooter transmissions.

PROPULS GEAR has as properties:

- ✓ increased shear strength
- ✓ low temperature transmission protection
- ✓ high viscosity index favoring easy passage of speeds
- ✓ suitable for self-locking limited slip (quad) bridges.

Characteristics	Méthods	Units	Values
Kinematic viscosity at 40°C	ASTM D7042	mm ² /s	98.1
Kinematic viscosity at 100°C	ASTM D7042	mm ² /s	15.9
Viscosity index	ASTM D2270	-	174
Pour point	ASTM D97	°C	-42
COC flash point	ASTM D92	°C	>190

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document Ref : IV-IGOL010-1910

Published : 15/10/2019

