• Maintenance range

DKPAN

\bigcirc

Regenerates surfaces altered by the presence of solid or film-formed tailings

Stripping agent without methylene chloride, without N-methylpyrrolidone and without methanol (does not flow). Effective on a wide variety of paints and coatings. It strips varnishes and lasures removes graffiti and dissolves the majority of adhesives. Plastics processes: dissolves plastic material residues that can make moulds unsuitable for their purpose. Use on materials withstanding attacks from solvents (wood, brick, cement, iron and steel),

500 ml

DÉMARRAGE MOTEUR ECIAL FOR POOR ENGINE STARTING

Facilitates quick-start in all weathers for petrol or diesel engines.

Makes for easier engine startup. Prevents all risks of engine seizure: it works quickly to prevent the battery from draining. Can be used on all types of motors. 400 ml

REDUCTOL 8

😂 🚳 🔂 🚍 🚱 DUO SPRAY

Facilitates disassembly - Unjams - De-rusts - Lubricates - Anti-corrosion - Anti-moisture -Phosphating agent.

Reductol 8 is a multi-purpose penetrating oil. It reduces rust and descales transmission components making them easier to disassemble. Its special formula includes excellent descaling and cleaning agents, which means it can be handy for all types of maintenance work.

500 ml

DEGRIP AL

0

Multipurpose, high-performance release agent. It lubricates, loosens and facilitates disassembly work. Cleaning and humidity resistant properties. Protects parts from corrosion. Specially designed for use in the food industry. 400 ml

NSF.



ANTI

(3)

300 ml

OIL CUT

CREVAISON

Offers on-hand assistance by instantly

re-inflating both regular and tubeless tires

Repairs and instantly inflates tyres with inner tube or

tubeless tyres, with no tools or disassembly required.

Suitable for tyres on cars, motorcycles, scooters, trai-

lers, caravans, etc. Can be used to re-inflate all types

of car and motorcycle tyres (2 cans recommended for

expectancy of tools and machinery. With its high-pressure capabilities, can be used: - On ferrous and non-ferrous metals. - For any difficult operation (drilling, tapping, threading, boring).

- For all types of activities

400 ml



THERMO CONTACT KING ASSEMBLY PASTE

0

Avoids corrosion and thermal rust. Protects against seize-up. Lubricates at high temperaturess

Anti-seize paste made with aluminium complex soap specially designed to prevent seizing and corrosion. Makes it possible to easily assemble and disassemble parts subject to chemical or thermal treatment. There mocontact makes for better electrical contact. Lubri-cation from -30°C to +600°C.

400 ml

FILTER CROSS

23

Holds back dusts efficiently and protects the engine from abrasive wear. Highly adhesive lubricant spray for foam filter com-500 ml

SOUDNET

😁 🚷 🔂 🚍 🔂 💮

Protects nozzles. Prevents welding spatter from adhering. Silicon-free. Paint can be applied following use. Protects areas around welding. Chemically and thermally 400 ml



🗢 🚯 名 👄 🔂 🔗

High-performance, anti-corrosive release agent and lubricant Anti-seizing, lubrication and corrosion protection for all mechanisms and metal parts. Water and humidity resistant. Leaves a grease film that lubricates, protects and is very effective against corrosion. Suitable for long-term storage of metal parts. Reduces the coefficient of friction between the moving parts and the brackets. It dissolves greases and tars. This penetrating oil can be used in the following fields:

ndustrial, public works, farm machinery, etc. 500 ml

IGOL BRETAGNE ANJOU PA de la Forêt - BP 10 44140 LE BIGNON - FRANCE T. +33 (0)2 40 32 80 00 / F. +33 (0)2 40 75 11 54

IGOL CENTRE

72, rue d'Alsace Lorraine - CS 70002 58028 NEVERS CEDEX - FRANCE T. +33 (0)3 86 59 78 80 / F. +33 (0)3 86 59 14 88

IGOL PICARDIE ILE-DE-FRANCE 614, rue de Cagny - CS 19403 80094 AMIENS CEDEX 3 - FRANCE T. +33 (0)3 22 47 79 47 / F. +33 (0)3 22 46 79 61

DIVISION INDUSTRIE 614, rue de Cagny - CS 19403 80094 AMIENS CEDEX 3 - FRANCE

IGOL PROVENCE Z.I. de la Palun 13548 GARDANNE CEDEX - FRANCE T. +33 (0)4 42 51 78 00 / F. +33 (0)4 42 51 18 36

www.igol.com



IGOL.

IGO

LUBRICANTS





Find out more about IGOL by scanning the QR code via your smartphone.

RANGE OF

IGOL PICARDIE ILE-DE-FRANCE T. +33 (0)3 22 47 79 47 / F. +33 (0)3 22 46 79 61

IGOL EXPORT

Z.I. de la Palun 13548 GARDANNE CEDEX - FRANCE Sébastien Molina - Responsable Commercial Export : T. +33 (0)6 69 63 99 37 - sebastien.molina@igol .com Cécile Brugait - Assistante Commercial Export : T. +33 (0)3 22 95 95 83 - cecile.brugait@igol.com

IGOL FRANCE 614, rue de Cagny - CS 19403 80094 AMIENS CEDEX 3 - FRANCE T, +33 (0)3 22 50 22 22 / F, +33 (0)3 22 50 22 23

- Maintenance range
- Grease removal range
- Protection range 0
- Greasing and lubricating range
- Automotive cosmetics range



BANGE OF AEROSOLS

AEROSOLS... WHO ARE THEY FOR, AND WHY...? 📀 🐼 🕰 😂 🔂 😭

Range of aerosols designed to meet every requirement

All the products in this line have been researched and developed by IGOL, and comply with the strictest standards with respect to safety and the environment. This range of 35 products offers a tailored solution for every type of complex and demanding operating environment. Each business sector has its own set of products.

For even greater ease of use and effectiveness, try out the DUO-SPRAY IGOL nozzle. This new spraying development for IGOL aerosols ensures that the IGOL products you have chosen are used under the best possible conditions. The two spraying positions offered by the DUO-SPRAY nozzle give you both efficient control and precision when using the products delivered in aerosol form.

DISCOVER OUR NEW NOZZLES DUO-SPRAY

O Grease removal range



DUO SPRAY

General purpose grease remover, cleanser and descaler. General mechanics and automotive. Cleans and degreases mechanical parts brake pads and shoes, clutch components, and contacts for distributors and electrical terminals. Dissolves any deposits from resin, oil, grease, wax or brake fluids. 500 ml

NET FREINS

🕾 🚯 🕞

Special for braking and clutch systems. Removes brake fluid, grease, oil, dust and all oth

residue from metal parts. Restores adherence to disc seals on the engine flywheel clutch system. Enables the brake system to function correctly. Makes noises disappear. Leaves no residue.

)| D THE N077| F

500 ml

Leaves no residual deposits. Very short drying time. Compatible with most materials.

NET CONTACT

Degreasing of metal parts, bearings, moulds, machined parts. Cleaning of brake components (calipers/discs, etc.) - elastomer-compatible. Cleaning of mountings, frames, beams on machine tools. Degreasing of electric motors, fuses, circuit breakers (AT VOLTAGE LESS THAN 12000V). Can be used on most materials, including coated metals, laminates and thermoset plastics. Inert with respect to metals: does not cause oxidation on light alloys or metal ponents containing copper.

300 ml



ECISION SPRAY

DUO SPRAY

Colorless. Odorless. Specially designed for degreasing mechanical parts in the food industry. Complies with FDA 21 CFR 178.3530 requirements



O Greasing & lubricating range



SILGLISS **(**)

Ensures a long-lasting lubrication. Water-proofs and facilitates gliding. Synthetic, clean lubricant for all types of mechanisms. Glidant for industrial applications (belts, shrinkwrapper, Staken) - Helps with thermoplastic mould releas Lubrication for paper cutter platforms and blades (printing). Can be used for temporary protection through application of anti-rust film (for small steel composite parts)

400 ml SILGLISS AL

6

NSE

NSE

NSE Star

Ensures a long-lasting lubrication Waterproofs and facilitates sliding. A clean synthetic lubricant for all mechanisms in the food industry. Silicone-based glidant. For all delicate oreasing operations. 400 ml

LUBAL

0

General lubrication of machinery on lightweight service in the food industry Lubrication of mechanisms. Moving and hinged parts. Lubrication for packaging lines. Lubrication of food industry equipn 400 ml

GREASE GRV

63 🚱

Highly adhesive. Heavy loads. Totally insoluble in water or steam.

Bearings and slide bearings subject to vibrations and repeated impacts. Hinged mechanisms and chains working in extremely humid environments. Rails and cams. Geared mechanisms, both exposed and in casings. Mould ejectors. Highly adhesive on metal parts. Highly resistant to heavy loads. Totally insoluble in water and steam. Operating temperature -20 to +140°C. It is very resistant to oxidation. 500 ml

Exceptionally water-resistant (equipment put to work n water mud or adverse weather conditions For the general lubrication of machinery, tools, ball or roller bearings. Highly-adhesive on metals (lubrication required less requently). High mechanical stability. Exceptional



SUPER VOLCAN EP

😂 🚷 🔂 🚍 🔂 🚱

and exposed dears.

600 ml

500 ml

500 ml

Extreme pressure adhesive lubricant. Recommended for the lubrication of cables Highly-adhesive lubricant for all types of lubrication on exposed or external mechanisms, etc

PATE AS 450

Heavy pressures. High temperatures. Synthetic lubricant with high molybdenum disulphide content (over 50%). Resistant to high temperatures (up to +165°C with grease lubrication and +400°C with dry lubrication) and high pressure.

Lubrication for guides, rails, gears and valves. Strip free liner fitting. Run-ins with no scratching or seizing. Metal forming. Cutting tool treatment. Operating temperature: -30 to +400°C.



Does not corrode paint, displaces water and fights moisture thanks to its hydrophobic action Non-mineral oil-based lubricant specially designed for small equipment and transmission systems. Drip free for clean, precise work. Chlorine and silicon free. Highly recommended for work with ecologica

SHP 50+ 🖴 🚷 🕰 🖴 🔂 🚱

shearing strength. Total insolubility in water (boiling water and steam), enabling lubrication of equipment working in water, mud and inclement weather Excellent corrosion and rust resistance. Excellent high-pressure capabilities. Operating temperature: -20 to +140°C. 500 ml

VISCOCHAINE PRO

😂 🚷 🔂 🚍 🔂 😭

Viscous, highly adhesive synthetic product. Exceptionally water-resistant.

Highly adhesive, oil-based lubricant specially deve loped for lubrication of all types of chains (conveyor motorcycles, bicycles, etc.) as well as cables and ex posed gears. Reduces friction, increases service life of the chain and protects it from rust. Water resistant reduces noise made by chain. Operating temperature -20 to 145°C.

This lubricant does not contain silicon or any element that is not compatible with USDA H2 requirements 500 ml

GELFLOI

63 To be used in a damp environment. Charged with PTFE. Use between -20°C and +180°C Codex mineral oil, in gel format for use in humid environments. With PTFE additive (polytetrafluo

NSF

NSE

roethylene) Workshops, kitchens, bathrooms, all technical equipment rooms. Recommended for plumbing mechanical, automobile and cycle applications. Cal be used whenever a clean lubricant is needed. Can be eliminated with organic solvents.

400 ml

CHAINE AL

Avoids fouling and the formation of deposits. Excellent shear stability

Particularly suitable for lubrication of chains on conveyors, ball bearings, roller bearings, moving hook systems used in the food industry, such as slaugherhouses, meat industries, canning plants, bakerie

500 ml

PROPULS

2

Specially designed to lubricate all motorcycle chains

Oil-based lubricant, specially designed adhesive for greasing all chains on on- or off-road motorcycles, with or without O-rings, in extreme operating condi tions. Reduces friction, increases service life of the chain, is water-resistant and protects against rust Contains solvent to eliminate deposits and provide good penetration in rods and pins.

500 ml

FLUOX HT

6

High performance. High Temperature. Ensure a high clean lubrication between -35°C to +270°C. Withstand the effects of shearing and impacts, saline and wet atmosphere It is inert to oxygen. Silicone-free. Insoluble in petroleum solvents. Long lasting lubrication

250 ml

R CHAINE

DUO SPRAY

Ensure a long lasting lubrication. Clean lubricant. Temperature range -40°C to +210°C.

Synthetic aerosol fluid aimed at lubricating chains and conveyors working. Ensure a long lasting lubrication or devices in motion. Antiwear, extreme pressure. High thermal stability, and causes no deposits. Silicone-free and compatible with any petroleum-derived

500 ml

()

O Protection range



🙃 🚯 名 🖴 🚱

GALVATECH

Protects any non-coated metal part. Allows recovery of hot-dipped galvanized parts or recovery of parts after machining or welding. Cold-galvanization product, with high-purity zinc. Provides long-lasting protection to all ferrous metal or metal alloy parts. Creates a uniform film layer, resistant to temperatures of up to 550°C with no damage. Coating can be welded (except with argon), after film is created (24h at 25°C). Provides galvanic protection against all forms of thermal or chemical

500 ml

NET

2040 DW

🕾 🚷 🔂 🚍 🚱

Protects from humidity and displaces water Long-lasting protection. All industrial machinery Agriculture / Public Works / Aeronautics / Leisure (Hunting, etc.)

Rust protection : highly adhesive on metal, ensures long-lasting protection for coated surfaces. Degreasing agent : eliminates grease residue and impurities, and leaves behind a protective film Penetration agent : penetrates deep down to fight sub-laver corrosion and prevent the formation and development of pitting. Water repellant : has waterresistant properties. Repels water from contacts. Suitable for all applications (with no electrical voltage present) that need to be kept dry and protected Guaranteed silicon-free.

400 ml

Automotive cosmetics range

DEGIVRE

Eliminates frost on windscreens and rearview mirrors.

Fliminates frost from windshields windows headlights and rearview mirrors on cars and vehicles of all types. Also effective against frost in locks, hinges and door se

400 ml

RENOV **PLASTIQUE**

(3)

Silicon polish. Restores the gloss and shine of new materials.

Restores brilliance and shine, just like new. Specially developed for dashboards, bumpers, rubber furnishings on doors, paints, varnishes, casings on motorcycles, scooters and jet skis, etc. Leaves behind a protective antistatic film to repel dirt and water. Contains silicon to provide complete overall shine 500 ml

PLASTIQUE

Silicon-free polish. A subtle aroma of oranges for a regular, easy maintenance. Leaves no traces or residues.

Restores brilliance and shine just like new Specially developed for dashboards, bumpers, rubber furnishings on doors, paints, varnishes, casings on motorcycles, scooters and jet skis, etc. Leaves behind a protective antistatic film to repel dirt and water. DOES NOT CONTAIN SILICON.

500 ml

TISSU NET

🔁 🚍

Prevents dirt accumulation and revives upholstery materials Quick-acting foam. Eliminates stains. Absorbs dir Treats fibers

400 ml



NET VITRES

Cleaner with a strong degreasing power. Quick drying without leaving any trace or glare. Make shine and restore brightness for any glazed surfaces windows, mirrors, wind 1000 ml

IGOL

