






AUTOMOBILE RANGE





Ancestral values

Born from the intuition of a few astute and generous persons, IGOL has perpetuated the original spirit that moved its creators and has never given up on their values. 65 years down the line, product quality, a commitment to innovation, customer service, proximity and reactivity still characterize our course of action.



1950



1970



1990



2000

**We are sure to have
the lubricant you need.**

www.igol.com



Get connected to
the world of IGOL
with the flashcode

IGOL.

LUBRICANTS

APPROVED

manufacturer warranty



PROFIVE

Modern vehicles require engine lubricants that comply with manufacturer approvals, but above all allow to maintain and even improve the engine's performances and lifespan. With its PROFIVE range; IGOL caters perfectly to such demands. Born from complex formulations and recognized as being at the cutting edge of the latest industrial technology, the PROFIVE range is the brainchild of our R&D department, which constantly provides the technical answers to the challenges of the most demanding manufacturers. So we invite you to keep a step ahead with PROFIVE.

IGOL LUBRICANT	VISCOSITY	ACEA/API	SPECIFICATIONS
IGOL PROFIVE 508/509	0W-20	API SN	Approved VW 508.00/509.00
IGOL PROFIVE RN 17 FE	0W-20	ACEA C5	Approved Renault RN 17 FE
PROFIVE OV	0W-20	ACEA C5 API SN PLUS / SN-RC	Synthetic motor lubricant approved OPEL – VAUXHALL – FORD – FIAT CHRYSLER AUTOMOBILE (FCA)
IGOL PROFIVE VCC	0W-20	ACEA A1/B1/C5 API SM	VOLVO VCC RBS0-2AE
IGOL PROFIVE CRYSTAL	0W-30	ACEA C2	Approved Peugeot/Citroën - Automobiles B71 2312 - FIAT 9.55535-GS1& FIAT 9.55535-DS1
IGOL PROFIVE F950	0W-30	ACEA C2	Ford WSS-M2C950-A - Fiat 9.55535-GS1 - Fiat 9.55535-DS1
IGOL PROFIVE MZ	0W-30	ACEA C3	Approved MB-Approval 229.51 ; BMW LL-04
IGOL PROFIVE F948	5W-20	ACEA A1/B1 API SN	Approved FORD WSS-M2C948-B
IGOL PROFIVE ONYX	5W-30	ACEA C3 API SN	Approved MB-Approval 229.51 - BMW LL-04 / LL-01 - Approved VW 504.00 / 507.00 - PORSCHE C30
IGOL PROFIVE 504/507	5W-30	ACEA C3 API SN	Approved VW 504.00/507.00 - VW 503.00 / 506.01 / 502.00 / 505.00 / 505.01 - Mercedes-Benz MB 229.51 - PORSCHE C30 - BMW LL-04
IGOL PROFIVE D1 G2	5W-30	API SN ILSAC – GF-5	Approved dexos 1 GEN 2 n°D10732HL017 - Ford WSS-M2C-946-A
IGOL PROFIVE 2290	5W-30	ACEA C2	Approved PSA B71 2290-2017 – Fiat/Toyota : suitable for vehicles requiring a C2 lubricant
IGOL PROFIVE RN 17	5W-30	ACEA C3	Approved RENAULT RN 17
IGOL PROFIVE C4	5W-30	ACEA C3/C4	Approved RENAULT RN0720 - Mercedes-Benz MB 226.51/226.52
IGOL PROFIVE EMERAUDE	5W-30	API SN ACEA C3	Approved MB-Approval 229.51 - MB-Approval 229.52 - BMW LL-04 - Approved GM Dexos2 Licence number : RB2A1008017 - VW 502.00/505.00/505.01
IGOL PROFIVE SAPHIR	5W-30	ACEA C1/C2	FORD WSS-M2C934B - MAZDA (vehicles up to 2012) JAGUAR / LAND ROVER STJR.03.5005
IGOL PROFIVE F913	5W-30	ACEA A5/B5 ACEA A1/B1 API SL	Approved FORD WSS-M2C913-D - RENAULT RN 0700
IGOL PROFIVE DIAMANT	5W-40	API SM/SN ACEA C3	MB 229.51 - Mercedes-Benz MB 229.31/226.5 - Approved BMW LL-04 - Approved PORSCHE C40 - Approved RN0700/0710 - FORD WSS-M2C-917A - FIAT 9.55535.S2 - VW 502.00/505.00/505.01 - GM Dexos2
IGOL SYMBOL CERAMIC	5W-40	ACEA A3/B4 API SN/SM	Approved Renault RN 700/0710 - Mercedes-Benz 226.5 / 229.5 - OPEL GM -LL-B-025 - VW 502.00/505.00 - Porsche A40 - FIAT 9.55535.M2 - PSA B71 2296
IGOL PROFIVE B4R	10W-40	ACEA A3/B4 API SN	Approved RN 0700/0710 - VW 502.00/505.00 - Mercedes-Benz 229.3 - PSA B71 2300

IGOL.

LUBRICANTS

LEVEL

manufacturer warranty



PROCESS

Whatever your needs or your applications, with over 65 years of experience and innovation, IGOL is the first French free agent who can offer you the guarantee and quality of its lubricants. The PROCESS range is one of its flagships. You can rely on IGOL's experience and know-how to protect your engine on a daily basis and maximize your equipment's lifespan and performances, even in extreme conditions, thanks to its protection and reliability level.

IGOL LUBRICANT	VISCOSITY	ACEA/API	SPECIFICATIONS
PROCESS HYBRID FE	0W-16	API SN PLUS / SN-RC API SP	Low-viscosity synthetic motor lubricant, compatible with hybrid and gasoline engines. Complies with the requirements of TOYOTA - HONDA - SUZUKI
IGOL PROCESS HYBRID	0W-20	API SN ILSAC GF-5	Low-viscosity synthetic motor lubricant, compatible with hybrid engines. Complies with the requirements of North-American and Asian vehicles (Honda, Toyota...). Suitable for the most demanding conditions of use (city, road, motorway) and to high-revs sporty riding.
IGOL PROCESS V	0W-30	ACEA A5/B5 API SN ILSAC GF-4	Volvo 95200377
IGOL PROCESS RUBIS C2 C3	5W-30	ACEA C2/C3 API SN ILSAC GF-5	Mercedes MB 229.51/229.52 - GM Dexos 2 - BMW LL04 - VW 505.01 Fiat/Toyota : suitable for vehicles requiring a C2 lubricant.
IGOL PROCESS PLATINIUM	5W-30	ACEA C3	Mercedes-Benz MB 229.51 - BMW LL-04 - PORSCHE C30 - VW 504.00/507.00 - VW 503.00 /506.01/502.00/505.00/505.01
IGOL PROCESS SILVER	5W-30	ACEA C3 API SN	Mercedes-Benz MB 229.51/ 229.52 BMW LL-04 - DEXOS 2 - VW 502.00 / VW 505.01
IGOL PROCESS A5/B5	5W-30	ACEA A5/B5 ACEA A1/B1	A next-generation lubricant specially designed for the latest touring motor car engines, compliant with the new European requirements in the matter of carbon monoxide emission and energy saving.
IGOL PROCESS GOLD	5W-40	ACEA C3 API SN/SM	Mercedes-Benz MB 229.51/226.31/226.5 - BMW LL-04 - PORSCHE C40 - RN 0700/0710 - FIAT 9.55535.S2 - FORD WSS-M2C-917A - VW 502.00/505.01 - GM Dexos2
IGOL PROCESS S	5W-40	API SN ACEA A3/B4	Mercedes-Benz MB 229.1 - Renault RN0700
IGOL PROCESS B4	10W-40	ACEA A3/B4 API SL/CF	Mercedes-Benz MB 229.1
IGOL PROCESS CLASSIC	10W-40 15W-50	API SL/CF	Mercedes-Benz MB 229.1 - VW 501.01/505.00
IGOL PROCESS GS	15W-40 20W-50	API SG/CD	

IGOL.

LUBRICANTS

MOTOR RACING



Race Factory

The new range of lubricants dedicated to motor racing

Born from the experience in rally racing and tested under the most extreme conditions, this new range of IGOL RACE FACTORY lubricants is destined to provide the hyper performance of sports and upscale vehicles : muscular thoroughbreds, built to face challenges.

IGOL LUBRICANT	VISCOSITY	ACEA/API
IGOL RACE FACTORY RALLYE	5W-50	ACEA A3/B4 - API SL

SPECIFICATIONS :

Mercedes-Benz MB 229.1 - VW 502.00/505.00.

100% synthetic lubricant for race engines. Excellent protection of moving mechanical parts. Suitable for 4-stroke petrol-fuelled atmospheric and turbo compressed engines. Perfectly adapted for medium-duration events : track racing or rally.

IGOL LUBRICANT	VISCOSITY	ACEA/API
IGOL RACE FACTORY COMPETITION	10W-60	ACEA A3/B4 - API SL

SPECIFICATIONS :

100% Ester and PAO (Polyalphaolefin) based, high performance motor oil, specially designed for powerful, sporty, hard-driven and high-revving engines, both for road and track racing. Suitable for all types of petrol or diesel engines, turbo-charged or not, running on all types of fuels, leaded or unleaded, gasoil and LPG, fitted or not with a catalytic converter. Suitable for some BMW, PORSCHE, etc. engines.

IGOL LUBRICANT	VISCOSITY	ACEA/API
IGOL RACE FACTORY RACING	0W-40	ACEA A3/B4 - API SN

SPECIFICATIONS :

FORD WSS M2C 937-A - MB 229.3 & 229.5, PORSCHE A40, BMW LL-01, RN700 & 710, VW 502.00 & 505.00, MS12633, MS10725

Synthetic, PAO-based lubricant, low viscosity and high resistance to extreme operating conditions. Recommended whenever the FORD WSS M2C 937-A standard is required, notably with Ford Focus RS 2.5L TURBO Duratec vehicles. For high-powered, high-revving and sporty-driven petrol or diesel engines. Compatible with catalytic converters and particle filters (Mid SAPS).

IGOL.
LUBRICANTS

HISTORY
lives on...



Héritage
SINCE 1949



Multi-grade lubricant for vintage engine and collector vehicle

For over 65 years, IGOL has always spelled safety and guaranteed peace of mind. The HERITAGE range of lubricants blends the very spirit of those years of research and technical experience, serving performance and engine protection. With HERITAGE, IGOL today offers the answer in terms of lubricants fully adapted to the needs of fans of historical motors, vintage collectors or youngtimers.

IGOL LUBRICANT	VISCOSITY	API / ACEA	COMPOSITION
IGOL HÉRITAGE ZS	15W-50	API SL/CF	SEMI-SYNTHETIC LUBRICANT

SPECIFICATIONS :

Mercedes-Benz MB 229.1 - VW 501.01/505.00

Lubricant for petrol-fuelled touring engine, reinforced in synthetic bases, particularly suited to vintage vehicles.

IGOL HÉRITAGE GTZ	20W-50	API SF/CF	MINERAL LUBRICANT
-------------------	--------	-----------	-------------------

SPECIFICATIONS :

Multi-grade lubricant complying with API SF/CF standard for petrol and diesel engines, developed from mineral bases and additives suited to vintage engines (from 1950 up).

IGOL HÉRITAGE SPORT	SAE 30 SAE 40 SAE 50	API SE/CC	MINERAL LUBRICANT
---------------------	----------------------------	-----------	-------------------

SPECIFICATIONS :

Monograde oil, antioxidant and antiwear, for the lubrication of petrol-fuelled engines.

IGOL HÉRITAGE GRAMO B	80W-90	API GL-5	MINERAL LUBRICANT
-----------------------	--------	----------	-------------------

SPECIFICATIONS :

MIL-L-2105D

A multi-grade lubricant for older-generation vehicle gearboxes and axles subject to very tough engine speeds.



IGOL.
LUBRICANTS

Transmission Gears and axles



TRANSMISSIONS GEARS AND AXLES

IGOL.
LUBRICANTS

IGOL PRODUCT	SPECIFICATIONS
IGOL PREMIUM GEAR API GL-4 OIL FOR MANUAL TRANSMISSIONS AND BRIDGES Viscosity : 75W-90 Viscosity : 75W-80	Specific lubricant for motorcar gearboxes. API GL-4. Not suitable for AUDI which requires an API GL-5. Grade 75W-90 : Lancia, Ford, Chevrolet, Opel, Saab, Hyundai, Kia, Mazda, Mitsubishi, Nissan, Suzuki, Land Rover, Jaguar, Toyota. Grade 75W-80 : Mini, Mercedes, Smart, Alfa Romeo, Fiat, Volvo, Honda, Rover, Citroën, Peugeot, Dacia, Renault, Seat, Skoda, Volkswagen.
IGOL RALLYE GEAR API GL-4/GL-5 - MIL-PRF-2105E OIL FOR MANUAL TRANSMISSIONS AND BRIDGES Viscosity : SAE 75W-80 Viscosity : SAE 75W-90 Viscosity : SAE 80W-140	Specific lubricant for gearboxes and transfer cases. Developed to comply to the TDL concept (Total Drive Line). Grade 75W-80 : for mechanical gear-boxes.. Grade 75W-90 : for mechanical gearboxes and all transfer cases including limited-slip ABS. Grade 80W-140 : for all axles, in particular limited-slip subjected to heavy loads.
IGOL GEAR FLUID FE GL4/GL5 - 75W OIL FOR MANUAL GEARBOXES	Complies with the following specs : VW 052 178/ 052 512/ 070 726/ 052 527/ 070 726, BMW 8322 2409 710/ 8322 0 397 244/ 8322 0 306 816/ DTF 1 (83 22 2 409 710), Fiat 9, 55550 MZ6 75W, WSS-M2C 200-D2, Nissan LVMT1 75W
IGOL DUAL GEAR OIL OF DOUBLE CLUTCH BOXES IMMERSÉ	AUDI VW TL 052 182 / VW TL 052 529 - BMW (GETRAG) 83 22 2 148 578 / 83 22 148 579 / 83 22 0 440 214 / 84 83 22 2 147 477 - FORD M2C936A - PEUGEOT / CITROEN 9734. S2 - Mercedes-Benz MB 236.21 - MZ 320065 DIA QUEEN SSTF-I - PORSCHE OIL No 999.917.080.00 - Volvo 1161838 / 1161839
IGOL ATF VI FLUID FOR AUTOMATIC TRANSMISSION	Approved GM DEXRON®-VI - License number J-60399 - AISIN WARNER AW-1 - ALLISON C-3, C-4 - ESSO LT 71141 - CHRYSLER +4 - FORD MERCON® SP - GM TYPE A, SUFFIX A (TASA) - GM DEXRON®, -II, -IID, -IIE, -IIIF, -IIIG, -IIIH - JASO 1-A - JWS 3309 - MAN 339 TYPE V-1 /MAN 339 TYPE Z-1 - MB 236.1 / MB 236.41/ MB 236.5 - MITSUBISHI / HYUNDAI / KIA SP III - HYUNDAI / KIA SP IV - NISSAN MATIC-S - SHELL M115 - TEXACO ETL-7045E / TEXACO ETL-8072B - TOYOTA T-IV, WS - VICKERS M-2950-S, I-286-S - VOITH 55.6335.XX - VOLVO 97341 - ZF TE-ML -09, -11B, AND - 14A - VW G052 171 ; VW G052 178 ; VW G052 512 ; VW G052 726 ; VW G060 726 - Audi G 052 162 (ZF Lifeguardfluid 5) (ZF No. S671 090 170) Audi/VW G 052 990 ISUZU BESCO - ATF SP ISUZU SCS Fluid Jaguar ATF 3403 JLM20238, Renault Samsung SATF-D VW G 052 162 - (ZF Lifeguardfluid 5)
IGOL ATF MULTI FE LOW VISCOSITY FLUID FOR AUTOMATIC TRANSMISSIONS	Complies with the following specs : MB 236.14 / 236.12 / 236.10 /236.3 / 236.6 / 236.7 / 236.8 / 236.9 / 236.11 / 236.91- ALLISON C4 - BMW 83 22 2 152 426 - CHRYSLER ATF +3 - HONDA Z-1 - HYUNDAI SP-II / SP-III - ISUZU ATF II / III - JAGUAR JLM 20238 / 20292 / 21044 - JASO TYPE 1A - KIA SP-II / SP-III - MAZDA M-III / TYPE T-IV - MITSUBISHI SP-II / SP-III / ATF J-2 - NISSAN MATIC D / J / K / W - SUBARU ATF / ATF HP - SUZUKI ATF 3314 / 3317 - TOYOTA TYPE DII / T / T-III / T-IV - VAG G-055-025 / G-052-162 - VOLVO 1161540
IGOL ATF MULTI SYNTHETIC FLUID, HIGH PERFORMANCE, HIGH VISCOSITY, MULTI VEHICLES FOR AUTOMATIC TRANSMISSIONS, POWER STEERING AND HYDRAULIC CIRCUITS	Specifications : refer to technical data sheet
IGOL ATF CVT FLUIDS FOR AUTOMATIC TRANSMISSIONS OF TYPE CVT (CONTINUOUSLY VARIABLE TRANSMISSION)	TOYOTA (TC) - NISSAN (NS-II) -MITSUBISHI (NS-II/SP-III) - SUBARU (NS-II) -DAIHATSU (TC) - HYUNDAI/KIA (SP-III) - SUZUKI (TC/NS-II) - DODGE CALIBE (NS-II) - GM/SATURN (DEX-CVT) - FORD (CVT-23) -Mercedes Benz (236.20)
IGOL ATF 700 FLUID FOR AUTOMATIC TRANSMISSION	Approved : ZF TE-ML 04D, 14B, 16L, 17C Complies with the following specs : GM DII, DIII (G), DIII (H) ; Jaso M314-2004 Suitables for : Voith 55.6335.xx ; MAN 339V1, 339Z2 ; ZF TE-ML 03D 04D 14A ; Allison C4 / TES-295 ; BMW LT71141, LA2636, ETL-7045, 8072B ; Caterpillar TO-2 ; Chrysler +3, +4 ; Ford M / M.V ; HMC/KIA SP-III ; Honda Z1 ; Jaguar Idemitsu K17 ; Land Rover Texaco N402 ; Mazda ATF M-III, M5 ; Nissan Matic D, J, K ; Subaru ATF, Plus ATF-HP ; Toyota T-III, T-IV ; Volvo Std 1273.4 ; VW/AUDI G 052 025 (09M), G052 990 (09A) ; FIAT 9.55550.AG2 ; Voith-DIWA H55.633644
IGOL ATF 430 FLUID FOR AUTOMATIC TRANSMISSION	G. M. DEXRON III H - MERCON - GM Type A Suffix A (TASA) - Allison C-4 / TES-389 - ZF TE-ML 02F 03D 04D 05L 09 11B 14A 17C 21L - Voith 55.6335xx - MAN 339 Z1 / 339 V1 - MB p.236.1 / 236.5 / 236.9 - VOLVO 97341 - FIAT 9.55550.AG1 & FIAT 9.55550.AG2
IGOL BLOCK DA POWER STEERING AND HYDRAULIC POWER STATIONS	MAN M 3289 - Mercedes-Benz MB 345.0 - VW TL 521 46 (VW G 002 00/A7/A8/G 040 000) - OPEL 1940 715/766 - PSA S71 2710

Vos contacts régionaux

IGOL BRETAGNE ANJOU

PA de la Forêt - BP 10
44140 LE BIGNON - FRANCE
T. +33 (0)2 40 32 80 00
F. +33 (0)2 40 75 11 54

IGOL CENTRE

72, rue d'Alsace Lorraine - CS 70002
58028 NEVERS CEDEX - FRANCE
T. +33 (0)3 86 59 78 80
F. +33 (0)3 86 59 14 88

IGOL PICARDIE ILE-DE-FRANCE

614, rue de Cagny - CS 19403
80094 AMIENS CEDEX 3 - FRANCE
T. +33 (0)3 22 47 79 47
F. +33 (0)3 22 46 79 61

IGOL PICARDIE ILE-DE-FRANCE

Division Industrie
614, rue de Cagny - CS 19403
80094 AMIENS CEDEX 3 - FRANCE
T. +33 (0)3 22 47 79 47
F. +33 (0)3 22 46 79 61

IGOL PROVENCE

Z.I. de la Palun
13548 GARDANNE CEDEX - FRANCE
T. +33 (0)4 42 51 78 00
F. +33 (0)4 42 51 18 36

IGOL RHÔNE-ALPES

4, rue de l'Ozon
69360 SÉRÉZIN-DU-RHÔNE - FRANCE
T. +33 (0)4 78 02 39 00
F. +33 (0)4 78 02 02 83

IGOL EXPORT

Z.I. de la Palun
13548 GARDANNE CEDEX - FRANCE
T. +33 (0)4 42 51 78 00
F. +33 (0)4 42 51 18 36

IGOL FRANCE

614, rue de Cagny - CS 19403
80094 AMIENS CEDEX 3 - FRANCE
T. +33 (0)3 22 50 22 22
F. +33 (0)3 22 50 22 23