

100% synthetic* lubricant for automatic CVT transmissions.

ADVANTAGES and USES

A CVT (Continuously Variable Transmission), is a type of automatic transmission used on some cars that theoretically allows an infinite number of transmission ratios between the shortest and longest ratios, its operating principle can vary depending on the manufacturer: magnetic, toroidal, chain or belt (the most common).

IGOL ATF CVT is a high-tech universal lubricant specially designed for these continuously variable automatic gearboxes.

Its 100% synthetic* and specific formulation offers the following advantages:

- Reduction of vibrations and chattering sensations
- · Fast and smooth gear shifting
- Excellent low and high temperature properties
- Resistance and protection against wear and corrosion
- Fuel-efficient performance due to reduced friction between belt/chain and pulley
- Multi-generation product

IGOL ATF CVT is suitable for a large number of manufacturers' specifications and therefore for many applications (see page 2 for a non-exhaustive list). Not suitable for CVT transmissions in hybrid vehicles.

PHYSICO-CHEMICAL PROPERTIES

Characteristics	Standards	Units	Values
Density at 15°C	ASTM D4052	g/cm3	0.845
Kinematic viscosity at 40°C	ASTM D7042	mm²/s	35.4
Kinematic viscosity at 100°C	ASTM D7042	mm²/s	7.3
Viscosity Index	ASTM D2270	-	177
Pour Point	ASTM D97	°C	- 42
Flash Point	ASTM D92	°C	214



Documentary reference: IV-IGOL045-2204

Date of issue: 17/06/2022



IGOL ATF CVT — Applications		
Manufacturer	Specifications	
ТОУОТА	CVTF TC / FE	
FORD	WSS-M2C928-A	
BMW - MINI	EZL 799A	
CHRYSLER / DODGE	MOPAR CVTF+4 / NS-2	
MERCEDES	MB 236.20	
MITSUBISHI	CVTF-J1 / CVTF-J4 / CVTF-J4+ / SP III (CVT models only)	
NISSAN	Fluide CVT NS-1 / NS-2 / NS-3	
GENERAL MOTORS	1940713 / 1940714 / DEX CVT	
HYUNDAI / KIA	CVT-J1	
HONDA	HMMF / HCF.2	
DAIHATSU	AMMIX CVTF DFE	
SUZUKI	CVTF 3320 / CVTF TC / NS-2 / GREEN 1 / GREEN 2	
SUBARU	ECVT / iCVT / iCVT FG / Lineartronic	
Groupe VOLKSWAGEN	Audi Multitonic VW G 052 180 / VW G 052 516	

*Contains HydroCracked (HC) base oils

Note: Before use, always check the manufacturer's recommendations in the maintenance manual.

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

THE LUB RIVERS OF THE PARTY OF