

PREMIUM GEAR + 75W-80

High performance semi-synthetic lubricant for manual gearboxes.

PERFORMANCES

Standards:

API GL-4 / GL-4 + ZF TE-ML 02A / 06 / 08 / 17A

ADVANTAGES

IGOL PREMIUM GEAR + 75W-80 ensures and optimises the lubrication of manual gearboxes of passenger cars and certain light commercial vehicles in all conditions of use.

Its exclusive formulation gives it the following advantages:

- ✓ Excellent fluidity and viscosity stability at low and high temperatures
- Remarkable extreme pressure and anti-wear properties
- ✓ Smooth gear shifting.
- Increased gearbox life
- ✓ Compatible with all metals

USES

IGOL PREMIUM GEAR + 75*W*-80 is a versatile, multi-vendor product that is recommended for use in a wide range of gearboxes where API GL-4 / GL-4 + and SAE 75W-80 are required.

It offers the possibility of rationalising different manufacturers's specifications on the same product, for example:

BMW MTF LT-2 - FIAT 955550-MZ-6 - GM 1940768 - HONDA MTF / MTF-II / MTF-III - MTF 94 -NISSAN MT-XZ - NISSAN MT-XZ, type TL/JR - PSA B71 2330 / 2315 - TRANSELF NFJ (boites de vitesse JBX, JCX, JHX, JRX, NDX, TLX) - TRANSELF NFP (boites de vitesse PKX, PFX, VMX, NEX, NGX, NOX, UNX) - TRANSELF TRJ - VW G009 317 - FORD-M2C-186-A GM1940764- MB 235.10 -TRANSELF TRT / TRZ - VOLVO 97308 / 97309



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com



PREMIUM GEAR + 75W-80

PHYSICO-CHEMICAL PROPERTIES

Characteristics	Standards	Units	Values
Density at 15°C	ASTM D4052	g/cm3	0.860
Kinematic viscosity at 40°C	ASTM D7042	mm²/s	51.7
Kinematic viscosity at 100°C	ASTM D7042	mm²/s	9.2
Viscosity Index	ASTM D2270	-	162
Pour Point	ASTM D97	°C	- 46
Flash Point	ASTM D92	°C	218

Note: Before use, always check the manufacturer's recommendations in the maintenance manual.

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : IV-IGOL046-2209 Date of issue : 20/09/2022



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com