







WHO ARE WE?











1950

1970

1990

MORE THAN 70 YEARS OF PASSION AND STILL GOING STRONG!

The IGOL brand was created when fifteen heads of independent producers and distributors of lubricants across France joined forces. Since then, the company has grown steadily and is now one of the leading independent manufacturer of lubricants.

Our perennial priorities have been: quality, innovation and close working relationships - all with a view to fostering an effective partnership with every customer.



IGOL has always been involved in motor sports, competing at the highest levels. Rallying and motorcycle racing are embedded in the brand's DNA. Competitive racing provides an ideal and challenging proving ground for innovative lubricants. IGOL is proud to support the performance and achievements of its partners, by enabling them to exceed their expectations.





AN EXPORT DEDICATED TEAM

IGOL INTENSIFIES ITS INTERNATIONAL PRESENCE!

For more than 70 years, IGOL has been designing, developing and manufacturing innovative, state-of-the-art products.

IGOL offers a wide range of lubricants for engines, transmissions and gearboxes, but also complementary products such as greases, coolants, aerosols, cleaning products and cosmetics for all sectors of activity (Automotive, Motorcycle, Agriculture, Industry...).

With a brand new plant based in the north of France, IGOL continues to invest in research and development and in its production facilities to offer you premium products and services.



IGOL exports its French know-how to many countries.

IGOL and its dedicated Export team can help you to grow your business by benefiting from a strong brand with a presence in many international motorsports competitions, state-of-the-art products tailored to your needs and your market, tailor-made marketing tools and actions.



DO YOU WANT TO BECOME A DISTRIBUTOR OF THE IGOL BRAND OR TO KNOW MORE?

Please contact our dedicated export team!

By telephone: +33 6 69 63 99 37

By email: export@igol.com

OUR RANGES



Top-end lubricants that preserve OEM warranties and meet the latest ACEA standards.



Lubricants specially developed for competition.



Lubricants whose properties meet manufacturers' recommendations.



IGOL know-how applied to lubricants for older vehicles.





APPROVED OEM WARRANTY



Modern vehicles need engine lubricants that satisfy the approval criteria set by manufacturers, but which above all maintain and even improve engine performance and lifespan.

With its PROFIVE range, IGOL caters perfectly to these requirements. Our R&D department finds technical solutions that meet the most challenging demands imposed by manufacturers - this is particularly true for the cutting-edge industrial technology applied by this department to develop the complex formulations found in our PROFIVE range. Keep a step ahead with PROFIVE.

IGOL LUBRICANT	VISCOSITY	ACEA/API	SPECIFICATIONS
PROFIVE LOW SAPS RANGE			
IGOL PROFIVE HYBRID	0W-8		JASO GLV-1
IGOL PROFIVE 508/509	0W-20	API SN	Approved VW 508.00/509.00
IGOL PROFIVE 2010	0W-20	ACEA C5	PSA B71 2010
IGOL PROFIVE OV	0W-20	ACEA C5 API SN PLUS / SN-RC	Approved OPEL - VAUXHALL - FORD - FIAT - CHRYSLER AUTOMOBILE (FCA)
IGOL PROFIVE VCC	0W-20	ACEA A1/B1/C5 API SM	VOLVO VCC RBS0-2AE
IGOL PROFIVE PREMIUM TECH FE	0W-20	ACEA C5/C6 API SN PLUS / SP	DAIMLER Approved MB-Approval 229.71 - Opel/Vauxhall OV 0401547 - GM Dexos D - Ford F952-A - Jaguar STJLR.03.5006
IGOL PROFIVE 504/507	0W-30	ACEA C3	VOLKSWAGEN VW 504.00/507.00 - PORSCHE C30
IGOL PROFIVE CRYSTAL	0W-30	ACEA C2	Approved Peugeot/Citroën - Automobiles B71 2312 - FIAT 9.55535-GS1& FIAT 9.55535-DS1







IGOL PROFIVE F950	0W-30	ACEA C2	Ford WSS-M2C950-A - Fiat 9.55535-GS1 - Fiat 9.55535-DS1
IGOL PROFIVE MZ	0W-30	ACEA C3	Approved MB-Approval 229.51; BMW LL-04
IGOL PROFIVE F948	5W-20	ACEA A1/B1 API SN	Approved FORD WSS-M2C948-B
IGOL PROFIVE PREMIUM TECH	5W-30	API SP ACEA C3	MB-Approval 229.52 - MB-Approval 229.51 - Approved BMW LL-04 - Approved VW 504.00/ 507.00 - PORSCHE C30
IGOL PROFIVE 2290	5W-30	ACEA C2	Peugeot/Citroën Automobiles B71 2290-17 Fiat 9.55535.S1 - Iveco 18-1811 SC1
IGOL PROFIVE RN 17	5W-30	ACEA C3	Approved RENAULT RN 17
IGOL PROFIVE RN 17 FE	0W-20	ACEA C5	Approved RENAULT RN 17 FE
IGOL PROFIVE D1 G2	5W-30	API SN ILSAC – GF-5	Approved Dexos 1 GEN 2 No. D10732HL017 - Ford WSS-M2C-946-A
IGOL PROFIVE DIAMANT	5W-40	API SM/SN ACEA C3	MB 229.51 - Mercedes-Benz MB 229.31/ 226.5 - Approved BMW LL-04 - Approved PORSCHE C40 - Approved RN0700/0710 - FORD WSS-M2C-917A - FIAT 9.55535.S2 - VW 502.00/505.00/505.01 - GM Dexos2
IGOL PROFIVE HI TECH	5W-30	ACEA C3 API SN	MB-Approval 229.52 - MB-Approval 229.51 Approved BMW LL-04 (N20) - GM DEXOS 2 - VW 505.00/505.01
IGOL PROFIVE SAPHIR	5W-30	ACEA C1/C2	FORD WSS-M2C934B MAZDA (vehicles up to 2012) JAGUAR/LAND ROVER STJR.03.5005
IGOL PROFIVE C4	5W-30	ACEA C3/C4	Approved RENAULT RN0720 - Mercedes-Benz MB 226.51/226.52
PROFIVE FULL SAPS RANGE			
IGOL SYMBOL CERAMIC	5W-40	ACEA A3/B4 API SN/SM	Homologué Renault RN 700/0710 - Mercedes- Benz 226.5 / 229.5 - OPEL GM -LL-B-025 - VW 502.00/505.00 - Porsche A40 - FIAT 9.55535.M2 - PSA B71 2296
IGOL PROFIVE B4R	10W-40	ACEA A3/B4 API SN	Approved RN 0700/0710 - VW 502.00/505.00 Mercedes-Benz229.3 - PSA B71 2300
IGOL PROFIVE F913	5W-30	ACEA A5/B5 ACEA A1/B1 API SL	Approved FORD WSS-M2C913-D RENAULT RN 0700











With more than 70 years of experience and innovation under its belt, IGOL caters for all requirements and applications. It is the leading French independent producer and OEM have recognised the quality of IGOL's lubricants by designating them as "approved" products in terms of maintaining OEM warranties. The PROCESS range is an example of this quality.

You can rely on IGOL's experience and know-how to protect your engine and maximise your equipment's lifespan and performance, even under extreme conditions, thanks to the high levels of protection and reliability offered by the lubricants.

IGOL LUBRICANT	VISCOSITY	ACEA/API	SPECIFICATIONS	
PROCESS MID & LOW SAPS R	PROCESS MID & LOW SAPS RANGE			
IGOL PROCESS RUBIS C2 C3	5W-30	ACEA C2/C3 API SN ILSAC GF-5	Mercedes MB 229.51/229.52 - GM Dexos 2 - BMW LL04 - VW 505.01. Fiat/Toyota: suitable for vehicles that require a C2 lubricant	
IGOL PROCESS PLATINIUM	5W-30	ACEA C3	Mercedes-Benz MB 229.51 - BMW LL-04 - PORSCHE C30 - VW 504.00/507.00 - VW 503.00/506.01/502.00/505.00/505.01	
IGOL PROCESS GOLD	5W-40	ACEA C3 API SN/SM	Mercedes-Benz MB 229.51/226.31/226.5 - BMW LL-04 - PORSCHE C40 - RN 0700/0710 - FIAT 9.55535.S2 - FORD WSS-M2C-917A - VW 502.00/505.01 - GM Dexos2	
IGOL PROCESS SILVER	5W-30	ACEA C3 API SN	Mercedes-Benz MB 229.51/ 229.52 BMW LL-04 - DEXOS 2 - VW 502.00 / VW 505.01	





PROCESS FULL SAPS RANGE

IGOL PROCESS HYBRID FE	0W-16	API SN PLUS / SN-RC API SP	A synthetic, low-viscosity engine oil, compatible with hybrid engines, which meets the requirements for hybrid/petrol vehicles made by Toyota, Honda and Suzuki
IGOL PROCESS HYBRID	0W-20	API SN ILSAC GF-5	A synthetic, low-viscosity engine oil, compatible with hybrid engines, which meets the requirements for North American and Asian vehicles (Toyota, Honda, etc.). Suitable for the most demanding driving conditions (urban, open road, motorways) and for sporty driving at high revs.
IGOL PROCESS V	0W-30	ACEA A5/B5 API SN ILSAC GF-4	Volvo 95200377
IGOL PROCESS A5/B5	5W-30	ACEA A5/B5 ACEA A1/B1	A state-of-the-art lubricant developed specially for the latest passenger car engines that satisfies the new European regulations on carbon dioxide emissions and fuel efficiency. Suitable for vehicles required to meet standard A5/B5
IGOL PROCESS S	5W-40	API SN ACEA A3/B4	Mercedes-Benz MB 229.1 - Renault RN0700
IGOL PROCESS B4	10W-40	ACEA A3/B4 API SL/CF	Mercedes-Benz MB 229.1
IGOL PROCESS CLASSIC	10W-40 15W-50	API SL/CF	Mercedes-Benz MB 229.1 - VW 501.01/505.00
IGOL PROCESS GS	15W-40 20W-50	API SG/CD	
		·	









THE NEW RANGE OF LUBRICANTS DEDICATED TO MOTOR RACING

The product of years of experience on rally cars and tested under the most extreme conditions, this new range of IGOL RACE FACTORY lubricants have been developed to cater for the ultra-high performance of sports cars, supercars, racing cars and muscle cars.



IGOL LUBRICANT	VISCOSITY ACEA/API	SPECIFICATIONS	
IGOL RACE FACTORY RALLYE	5W-50 ACEA A3/B4 API SL ESTER & PAO	A 100% synthetic, very low viscosity, ESTER- and PAO-based lubricant offering high resistance to extreme conditions of use. Recommended when compliance with the Ford WSS M2C-937-A standard is required, notably for Ford Focus RS 2.5L TURBO Duratec vehicles. For high-power petrol and diesel engines operating at high revs for sports driving. Compatible with catalytic converters and particulate filters (MID SAPS). Approved by MB 229.5 and Mercedes-Benz MB 229.3. FORD WSS M2C 937-A - MB 229.3 & 229.5, PORSCHE A40, RN700 & 710, VW 502.00 & 505.00.	
IGOL RACE FACTORY COMPETITION	10W-60 ACEA A3/B4 API SN ESTER & PAO	A 100% synthetic, high-performance ESTER- and PAO-based engine oil specially developed for powerful, sporty engines driven hard at high revs on both roads and race tracks. Suitable for all types of petrol and diesel engines, turbocharged or not, running on all types of fuel, leaded or unleaded, diesel and LPG, fitted or not with a catalytic converter. Suitable for some BMW, PORSCHE, etc. engines.	
IGOL RACE FACTORY 0101	10W-50 ACEA C3 ESTER & PAO	A 100% synthetic, ESTER- and PAO-based engine oil specially formulated for powerful, sporty engines driven hard at high revs. Increases power output while reducing friction and wear. Provides optimal lubrication under demanding conditions. Suitable for petrol and diesel engines, turbocharged or not, running on leaded or unleaded fuels, diesel and LPG, fitted or not with a catalytic converter and a particulate filter. Meets the Abarth 0101 standard.	
IGOL RACE FACTORY RACING	OW-40 ACEA A3/B4 API SN ESTER & PAO	A 100% synthetic ESTER- and PAO-based engine oil for racing engir Excellent protection of moving mechanical components. Suitable for 4-stroke naturally aspirated and turbocharged petrol engines. Perfectly suited to medium-duration events: track racing or rallying. Mercedes-Benz MB 229.1 - VW 502.00/505.00.	







MULTIGRADE LUBRICANTS FOR VINTAGE AND COLLECTOR CARS

For more than 70 years, the IGOL brand has been synonymous with safety and peace of mind. The HERITAGE range of lubricants gathers together the quintessence of these years of technical research and experience to protect and enhance the performance of these engines. IGOL's HERITAGE range provides a modern lubrication solution that meets the demanding requirements of enthusiasts for their vintage, classic and young timer cars.

IGOL LUBRICANT	VISCOSITY ACEA/API	TECHNOLOGY	SPECIFICATIONS
IGOL HÉRITAGE ZS	15W-50 API SL/CF	SEMI-SYNTHETIC LUBRICANT	Mercedes-Benz MB 229.1 - VW 501.01/505.00 An oil for passenger vehicle petrol engines, upgraded by synthetic bases specifically selected to cater for the needs of vintage vehicles.
IGOL HÉRITAGE GTZ	20W-50 API SF/CF	MINERAL LUBRICANT	A multigrade oil that meets the API SF/CF standard for petrol and diesel engines, produced from mineral bases and additives specially selected for engines from 1950 onwards.
IGOL HÉRITAGE SPORT	SAE 30 SAE 40 SAE 50 API SE/CC	MINERAL LUBRICANT	A monograde, anti-oxidant and anti-wear oil for the lubrication of petrol engines.
IGOL HÉRITAGE GRAMO B	80W-90 API GL-5	MINERAL LUBRICANT	MIL-L-2105D A multigrade lubricant for the gearboxes and axles of older vehicles driven hard at high revs.





TRANSMISSION, GEARBOX & AXLE

IGOL LUBRICANT	SPECIFICATIONS
GEARBOXES	
IGOL GEAR FLUID FE OIL FOR MANUAL GEARBOXES 75W GL4 / GL5	Conforms with the following specifications: VW 052 178/ 052 512/ 070 726/ 052 527/ 070 726, BMW 8322 2409 710/ 8322 0 397 244/ 8322 0 306 816/ DTF 1 (83 22 2 409 710), Fiat 9, 55550 MZ6 75W, WSS-M2C 200-D2, Nissan LVMT1 75W
IGOL PREMIUM GEAR+ A SEMI-SYNTHETIC LUBRICANT FOR MANUAL GEARBOXES Viscosity: 75W-80	API GL-4 / MIL-L-2105 - ZF TE-ML 02A/06L/17A - TE-ML 08 Conforms with the following specifications: Mini - Mercedes - Smart - Alfa Roméo - Fiat - Volvo - Honda - Rover - Citroën - Peugeot - Dacia - Renault - Seat - Skoda - Volkswagen (exception: note that Audi requires compliance with API GL-5).
AUTOMATIC TRANSMISSION	
IGOL DUAL GEAR OIL FOR OIL-BATH TYPE DUAL- CLUTCH GEARBOXES	AUDI VW TL 052 182 / VW TL 052 529 - BMW (GETRAG) 83 22 2 148 578 / 83 22 148 579 / 83 22 0 440 214 / 84 83 22 2 147 477 - FORD M2C936A-PEUGEOT / CITROEN 9734. S2 - Mercedes-Benz MB 236.21 - MZ 320065 DIA QUEEN SSTF-I - PORSCHE OIL No 999.917.080.00 - Volvo 1161838 / 1161839
IGOL ATF VI FLUID FOR AUTOMATIC TRANSMISSIONS	Approved GM DEXRON®-VI - License number J-60399 - AISIN WARNER AW-1 - ALLISON C-3, C-4 - ESSO LT 71141 - CHRYSLER +4 - FORD MERCON® SP - GM TYPE A, SUFFIX A (TASA) - GM DEXRON®, -II, -IID, -IIE, -IIIF, -IIIG, -IIIH - JASO 1-A - JWS 3309 - MAN 339 TYPE V-1 /MAN 339 TYPE Z-1 - MB 236.1 / MB 236.41 / MB 236.5- MITSUBISHI / HYUNDAI / KIA SP III - HYUNDAI / KIA SP IV - NISSAN MATIC-S- SHELL M115 - TEXACO ETL-7045E / TEXACO ETL-8072B - TOYOTA T-IV, WS - VICKERS M-2950-S, I-286-S - VOITH 55.6335.XX - VOLVO 97341 - ZF TE-ML -09, -11B, AND - 14A - VW G052 171; VW G052 178; VW G052 512; VW G052 726; VW G060 726 - Audi G 052 162 (ZF Lifeguardfluid 5) (ZF No. S671 090 170) Audi/ VW G 052 990 ISUZU BESCO - ATF SP ISUZU SCS Fluid Jaguar ATF 3403 JLM20238, Renault Samsung SATF-D VW G 052 162 - (ZF Lifeguardfluid 5)





IGOL ATF MULTI FE

LOW-VISCOSITY FLUID FOR AUTOMATIC TRANSMISSIONS

Conforms with the following specifications: MB 236.14 / 236.12 / 236.10 / 236.3 / 236.6 / 236.7 / 236.8 / 236.9 / 236.11 / 236.91- ALLISON C4 - BMW 83 22 2 152 426 - CHRYSLER ATF +3 - HONDA Z-1 - HYUNDAI SP-II / SP-III - ISUZU ATF II / III - JAGUAR JLM 20238 / 20292 / 21044 - JASO TYPE 1A - KIA SP-II / SP-III - MAZDA M-III / TYPE T-IV - MITSUBISHI SP-II / SP-III / ATF J-2 - NISSAN MATIC D / J / K / W - SUBARU ATF / ATF HP - SUZUKI ATF 3314 / 3317 - TOYOTA TYPE DII / T / T-III / T-IV - VAG G-055-025 / G-052-162 - VOLVO 1161540

IGOL ATF CVT

FLUID FOR CVT-TYPE AUTOMATIC TRANSMISSIONS (continuously variable transmission) TOYOTA (TC) - NISSAN (NS-II) - MITSUBISHI (NS-II/SP-III) - SUBARU (NS-II) - DAIHATSU (TC) - HYUNDAI/KIA (SP-III) - SUZUKI (TC/NS-II) - DODGE CALIBE (NS-II) - GM/SATURN (DEX-CVT) - FORD (CVT-23) - Mercedes Benz (236.20)

IGOL ATF MULTI

FLUID FOR AUTOMATIC GEARBOXES, POWER STEERING AND HYDRAULIC CIRCUITS A synthetic, high-performance, high-viscosity and multi-vehicle fluid for automatic gearboxes, power steering and hydraulic circuits.

IGOL BLOCK DA

POWER STEERING AND HYDRAULIC CIRCUITS MAN M 3289 - Mercedes-Benz MB 345.0 - VW TL 521 46 (VW G 002 00/ A7/ A8/ G 040 000) - OPEL 1940 715/766 - PSA S71 2710

GEARBOX AND AXLE

IGOL RALLYE GEAR

OIL FOR MANUAL GEARBOXES AND AXLES

Viscosity: SAE 75W-80 SAE 75W-90 SAE 80W-140

API GL-4/GL-5 - MIL-PRF-2105E

A special, semi-synthetic lubricant for gearboxes and transfer boxes. Developed to meet the requirements of the T.D.L. concept (Total Drive Line).

Grade 75W-80: for manual gearboxes.

Grade 75W-90: for manual gearboxes and all transfer gearboxes, including limited-slip positraction differentials.

Grade 80W-140: for all axles, particularly limited-slip axles, subject to heavy

Grade 80W-140: for all axles, particularly limited-slip axles, subject to heavy loading.



