

100% synthetic oil *.

IGOL PROFIVE ULTRA TECH FE 0W-20 is a new generation lubricant that meets and exceeds the requirements of many manufacturers and supports the latest engine technologies. Its very high quality composition, developed by the IGOL R&D laboratory, provides optimum lubrication for modern engines requiring a low viscosity lubricant and complying with BMW LL-17 FE+ technology.

SPECIFICATIONS

International norms:

ACEA C5, C6 BMW Longlife-17 FE+ * API SQ-RC MB-Approval 229.71 * ILSAC GF-7A

MB-Approval 229.72 * JAGUAR STJLR.03.5006 FORD WSS-M2C954-A1

* Approved quality.

Spécifications:

BMW Longlife-14 FE+ FORD WSS-M2C947-B1 FORD WSS-M2C962-A1 FIAT 9.55535-GSX CHRYSLER MS-12145 GM/OPEL OV 040 1547

ADVANTAGES

- Fuel economy and reduced emissions.
- Engine protection and increased longevity.
- Suitable for modern and hybrid engines.

PHYSICO-CHEMICAL PROPERTIES

Characteristics	Standards	Unit	Values
Specific gravity at 20°C	ASTM D4052	g/cm³	0.843
Cinematic viscosity at 40°C	ASTM D7042	mm²/s	42.3
Cinematic viscosity at 100°C	ASTM D7042	mm²/s	8.5
Viscosity index	ASTM D2270	-	182
HTHS at 150°C	ASTM D4683	сР	2.65
TBN	ASTM D2896	mgKOH/g	8.6
Pour point	ASTM D97 B	°C	- 51
Flash point	ASTM D92	°C	227

Note: Always check the manufacturer's recommendations in the service manual before use.

*Contains HydroCracked base oils

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage

