

Semi-synthetic oil.

High-performance lubricant for all types of engines, Petrol injection, multi-valve, Diesel, naturally-aspirated or turbocharged, using all types of fuel - petrol - diesel - LPG).

PERFORMANCES

Standards: ACEA A3/B4
API SP/SL

Specifications: VW 501.01/505.00

ORGANISATIONS and MANUFACTURERS - Scope of application -

ACEA A3/B4: for "High Performance" indirect Injection Petrol and Diesel engines.

API SP: The most restrictive level of API (American Petroleum Institute) standard for oils to meet the needs of new gasoline engine technologies: low speed pre-ignition (LSPI) and deposit formation.

API SL: Meets vehicle manufacturers' requirements from 2004 and older engines.

VW 505.00: level ACEA B3 for natural-aspiration or supercharged Diesel engines. Max. oil change at 15 000 Kms.

VW 501.01: for natural-aspiration Petrol and Diesel engines.

| Characteristics | Standards | Units | 15W-50 |
|-----------------|-------------|--------------------|--------|
| Density at 15°C | NF T 60-101 | kg/m ³ | 863 |
| Viscosity 40°C | ASTM D445 | mm ² /s | 121.5 |
| Viscosity 100°C | ASTM D445 | mm ² /s | 17.6 |
| Viscosity index | NF T 60-136 | - | 161 |
| Pour point | ASTM D2602 | °C | -41 |
| Flash point | NF T 60-118 | °C | 234 |

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref.: I-114-1907
Date of publication: 16/09/2025

